



MODEL AT-5000 EASYAPP

BATTERY POWERED ROTOR TELEMETRY

- Easy application and installation
- Small size – typically requires only 3 in (76.2 mm) radial envelope
- 95 hours for 1000 ohm and 75 hours for 350 ohm strain gages, continuous use
- Digital telemetry
 - high data integrity and noise immunity
 - exceeds legacy FM telemetry and slip rings
- Two systems (Channel A and B) can be used side-by-side for multi-channel requirements
- Manual shunt calibration invoked at transmitter

TYPICAL APPLICATIONS

- Torque testing for half-shafts / propshafts and driveshafts
- Replacement of slip rings and in-line torque transducers
- Torsional strain testing
- RTD temperature measurement
- Voltage measurement

TRANSMIT TRUE TORQUE DATA

A revolutionary advance in miniature telemetry, the AT-5000 Series replaces slip rings and legacy FM telemetry, offering a perfect solution for applications requiring dependable data retrieval off of rotating shafts and easy installation.

The AT-5000 EasyApp utilizes a small battery powered transmitter mounted using an aramid fiber strap to directly measure, digitize, and transmit true torque data from rotating half-shafts, driveshafts, and rotors of all sizes and speeds. The system is also used for temperature, voltage, and acceleration sensing.

The AT-5000 EasyApp uses a long-life lithium battery to excite a strain gage and to power the AT-5000 telemetry electronics on the rotating shaft. The small signal resulting from torque applied to the shaft is amplified, anti-alias filtered, and digitized (typically at 11 718 samples per second). The digital data is reliably RF transmitted off the rotating shaft to a nearby pickup coil, which is connected to a receiver. The receiver converts the digital data to an analog voltage output (adjustable from 0 +/- 1.0 to +/- 10 volts). This DC to 1 kHz (or optionally higher) bandwidth voltage output can be fed directly to a data acquisition system, FFT analyzer, or an oscilloscope.

SPECIFICATIONS	
Transmitter Modules - Sampling Rate / Typical Bandwidth	
Channel A Transmitter	7812 samples per second; DC to 1.2 kHz frequency response; 4 MHz transmitter
Channel B Transmitter	11 718 samples per second; DC to 1.2 kHz frequency response (DC to 5 kHz available); 6 MHz transmitter frequency. (Channel A and B units can be co-located for 2-channel use.)
Transmitter Module^[1]	
Non-linearity	<0.1% of full scale (typical)
Digital Resolution	12-bit (0.025% of full scale)
Gain Drift	100 PPM/°C typical, exclusive of external gain resistor
Offset Drift	0.7 μ V/°C typical (0 -85 °C)
Bandwidth	DC to 1.2 kHz (up to 5 kHz bandwidth available; AC coupling also available)
Power	Typically <4 mA current draw from 3.6 V battery, excluding sensor excitation
Temperature	-40 to 185 °F (-40 to 85 °C) High Temperature option is available
Battery	
Battery Voltage	3.6-volt open circuit; 3.4 volts loaded. Low battery indication is transmitted to receiver at approximately 2.7 volts.
Bridge Excitation	2/3 length AA. Single use Lithium battery. Note: Non-rechargeable batteries. Do not store or use in applications with exposure to >302 °F (150 °C) temperatures.
Battery Life	95 hours for 1000-ohm and 75 hours for 350-ohm strain gages, continuous use
Receiver	
Power	12 volts nominal (9 to 18 VDC) Optional AC power supply 90-240 VAC, 12 VDC output
Output Range, Signals, and Adjustments	\pm 10 volts. Output gain can be adjusted to allow lower outputs (i.e. 5 volts). (RSSI) Received Signal Strength Indicator -2 to +4 volts (antenna signal strength). Zero adjust, Gain adjust, and Unipolar/ Bipolar output selection.
Dimensions (H x W x D)	NEMA style box: 3 x 6 x 4.25 in (76.20 x 152.40 x 107.45 mm)
Temperature	32 to 125 °F (0 to 50 °C)
Pickup Coil Choices	
Flexible Loop	24" (610 mm) ID includes 10 ft cable to receiver
Rigid Brass Loop	Rugged 1/4" brass loop. 1.25" x 1.61" x 2.94" phenolic base. Includes 10 ft cable to receiver.

[1] Specifications are provided for a 2.81 mV/V typical input

Transmitter Modules - Sensor Inputs	
Full Bridge Strain Gage	Including other bridge-style transducers, including pressure transducers, resistive accelerometers, load cells, torque transducers, etc.
Temperature	Type K thermocouple is standard. Standard range is -58 to -750 °F (-50 to 400 °C). RTD sensors can also be used; contact Accumetrics.
Voltage	0 to 100 mV; external voltage divider can be provided for high voltage measurement. Up to 2700 V measure with optional external dropping resistor

Housing Information



Transmitter for > 0.9 in (22.86 mm) Diameters	
Radial Height	0.78 in to 0.87 in (19.80 mm to 22.10 mm)
Axial Length	2.0 in (50.80 mm)
Weight	0.185 lb (0.085 kg)



Transmitter for > 2.0 in (50.8 mm) Diameters	
Radial Height	0.67 in to 0.76 in (17.00 mm to 19.30 mm)
Axial Length	2.0 in (50.80 mm)
Weight	0.152 lb (0.067 kg)



Transmitter for > 8.0 in (203.2 mm) Diameters	
Radial Height	1.0 in to 1.1 in max (25.40 mm to 27.95 mm)
Axial Length	2.0 in (50.80 mm)
Weight	0.233 lb (0.11 kg)



6 British American Boulevard Suite 103-F, Latham, NY 12110 USA

Toll-Free in the USA: 888 684 0012

Phone: 1 518 393 2200 | Email: telemetry@pcb.com

Accumetrics, Inc. provides digital telemetry systems used in a variety of applications such as aerospace, marine, defense, agriculture, transportation, milling operations, energy, and power generation. Systems transmit sensor data from rotating structures using wireless techniques, preserving the integrity of the data even in environments with high levels of electromagnetic interference. Measurement solutions range from single channel products, such as strain gage torque measurements, to advanced custom multichannel systems. Accumetrics, Inc. is a subsidiary of PCB Piezotronics, Inc., and PCB® is a wholly owned subsidiary of MTS Systems Corporations.

© 2020 Accumetrics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLineSM is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States. All other trademarks are property of their respective owners.

DS-0187-revD-1020



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.