



HIGH RPM SHAFT TORQUE MEASUREMENT

TORQUE TELEMETRY OF A STRAIN GAGE SIGNAL AT 17000 RPM

Application: Aerospace High RPM Shaft Torque Measurement

Wireless torque telemetry of a strain gage signal at 17000 RPM

Industry: Aerospace


Product: [AT-4000](#) (legacy 12 bit system—see the new 16 bit [AT-4400](#))

Parameters measured: Torque

When the Naval Air Depot needed to measure torque on a 2” shaft OD running at 17000 RPM, Accumetrics was chosen. A metal clamp collar incorporating insulated disks for induction power was used. The system provided continuous digitizing at a rate of 26485 samples/sec of 12 bit data (note: the Accumetrics AT-4400 now provides the same sample rate for 16 bit data). The system provided greater accuracy and less EMI susceptibility than legacy FM telemetry systems.

Benefits:

- Metallic collar design for high G force
- Induction powered- no batteries
- EMI resistant digital telemetry
- Anti-aliased data
- Precision measurements with good bandwidths
- No slip rings; nothing to wear or maintain



The picture shows an aluminum clamp collar securing the Transmitter's single channel electronics module to the high speed shaft. To couple power to the rotating transmitter (and to retrieve the digital data stream coming back to the Receiver), a glass laminate assembly (larger diameter yellow disks) is interconnected to the aluminum collar. A simple pickup loop (not shown) was used to provide the power and data connection to a Receiver located 24 feet away.

Note: The AT-4000 12 bit system has been updated to the AT-4400, providing 16 bit digitizing at 26485 samples per second and unparalleled accuracy.

The AT-4400 can also be configured as an individual cylindrical transmitter module for center-of-shaft mounting.



6 British American Boulevard Suite 103-F, Latham, NY 12110 USA
Toll-Free in the USA: **888 684 0012**
Phone: **1 518 393 2200** | Email: telemetry@pcb.com

Accumetrics, Inc. provides digital telemetry systems used in a variety of applications such as aerospace, marine, defense, agriculture, transportation, milling operations, energy, and power generation. Systems transmit sensor data from rotating structures using wireless techniques, preserving the integrity of the data even in environments with high levels of electromagnetic interference. Measurement solutions range from single channel products, such as strain gage torque measurements, to advanced custom multichannel systems. Accumetrics, Inc. is a subsidiary of PCB Piezotronics, Inc., and PCB® is a wholly owned subsidiary of MTS Systems Corporations.

© 2019 Accumetrics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLine™ is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States. All other trademarks are property of their respective owners.

MD-0404 revNR 0719



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.