



NVH SOUND CORRELATION TO DRIVESHAFT TORQUE

**STRAIN GAGE MONITORING OF AUTOMOTIVE DRIVESHAFTS
FOR USE WITH NVH CORRELATION**

Application: NVH Sound Correlation to Driveshaft Torque

Wireless strain gage monitoring of automotive driveshafts for use with NVH correlation

Industry: Automotive

Product: [AT-5000 EasyApp](#)

Parameters measured: Torque

When a major Detroit automotive manufacturer wanted a convenient, accurate, and dependable way of studying the correlation of passenger compartment audible (“moan”) noise to driveshaft torque, the AT-5000 EasyApp was chosen. The AT-5000 monitored torque with 12 bit data collected continuously at 11718 samples per second. The AT-5000’s anti-alias filtering was altered from its normal DC to 1.2 kHz value to a 5 kHz value for this application. The torque data was recorded along with sound recordings from a passenger compartment microphone during vehicle operation on a test track. Data analysis software (not included with the AT-5000 EasyApp) provided correlation results immediately after the run, while still in the vehicle.

Test data was easily recorded, and the long battery life and ease of mounting of the AT-5000 EasyApp allowed the same studies to be quickly replicated in different vehicles.

Benefits:

- Easy installation
- Good bandwidth / sampling rates
- No data dropout
- Long battery life
- High data integrity and noise immunity



AT-5000 EasyApp
(Mounted on automotive Driveshaft)



Installation of AT-5000
2/3 Length AA Battery



AT-5000 End View
(showing gain resistor, shunt cal connector, and
gage connections)

The picture above left shows the rotating AT-5000 EasyApp Transmitter; the low profile transmitter is held on to the driveshaft with an aramid fiber strap. A simple flex loop is mounted concentrically around the transmitter for signal pickup. Simple body tape, and plastic ties were used to fasten the pickup loop to convenient structures under the vehicles. It is easily mounted to the driveshaft using an Allen wrench. On the right is a close up of the input side of the transmitter. The gain resistor is on the front of board as shown; the resistor (or the entire input board) can be easily changed to adjust the sensitivity of the system.

Note: The battery of an AT-5000 EasyApp allows up to 150 hours of continuous use with a 1000 ohm strain gage; 50 hours with a 350 ohm strain gage.

The AT-5000 single channel telemetry system can also be configured to measure voltage and temperature (RTD or type k thermocouple).



6 British American Boulevard Suite 103-F, Latham, NY 12110 USA
Toll-Free in the USA: **888 684 0012**
Phone: **1 518 393 2200** | Email: **telemetry@pcb.com**

Accumetrics, Inc. provides digital telemetry systems used in a variety of applications such as aerospace, marine, defense, agriculture, transportation, milling operations, energy, and power generation. Systems transmit sensor data from rotating structures using wireless techniques, preserving the integrity of the data even in environments with high levels of electromagnetic interference. Measurement solutions range from single channel products, such as strain gage torque measurements, to advanced custom multichannel systems. Accumetrics, Inc. is a subsidiary of PCB Piezotronics, Inc., and PCB® is a wholly owned subsidiary of MTS Systems Corporations.

© 2019 Accumetrics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLine™ is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States. All other trademarks are property of their respective owners.

MD-0410 revNR 0719



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.