



TUGBOAT DRIVE TORQUE

**TORQUE DATA FROM AN OFFSHORE TUGBOAT'S MAIN
PROPELLER DRIVESHAFT**

Application: Tugboat Drive Torque

Wireless telemetry provides torque data from an offshore tugboat's main propeller driveshaft

Industry: Marine

Product: [AT-4400](#)

Parameters measured: Torque

Torque measurement equipment on shipboard apparatus needs to be easily installed, highly reliable, and require little or no maintenance. An AT-4400 16 bit digital telemetry system was chosen for monitoring torque from a 12.5" diameter main driveshaft during studies of an offshore tug's engine efficiency (gas mileage). The telemetry system used induction power to eliminate any needs for replacing batteries. The 16 bit digital data provided dependable high signal integrity, high resolution data to the user. Digital data was transmitted back to a remote Receiver via the induction power cable; the Receiver supplied 0 +/- 10V data to the user's data acquisition and analysis system, which used the torque and other sensor data to compute engine operational efficiency.

The AT-4400 uses precision instrumentation amplifiers, anti-alias filtering and a 16 bit high resolution digitizer to capture on-rotor torque signals at a rate of 26,495 samples per second. The digital data (which is naturally very EMI resistant) is decoded at the remote receiver to an analog output signal. The AT-4 provides user-adjustable output stage amplification and filtering for further user flexibility.



AT-4400 Receiver showing gain, offset, symmetry, gain range, zero/added offset, and output filtering controls

The picture on the left shows an AT-4400 split clamp-on collar for the 12.5" main drive shaft. For ruggedness, a phenolic stationary pickup coil was used (mahogany colored outer shape). A tuning enclosure can be seen on the lower left. A rear view of the Receiver is shown on the right. The Receiver's front panel has the on-the-fly shunt calibration switch.

The AT-4400 can be also be supplied in component form for center of shaft mounting.



6 British American Boulevard Suite 103-F, Latham, NY 12110 USA
Toll-Free in the USA: **888 684 0012**
Phone: **1 518 393 2200** | Email: **telemetry@pcb.com**

Accumetrics, Inc. provides digital telemetry systems used in a variety of applications such as aerospace, marine, defense, agriculture, transportation, milling operations, energy, and power generation. Systems transmit sensor data from rotating structures using wireless techniques, preserving the integrity of the data even in environments with high levels of electromagnetic interference. Measurement solutions range from single channel products, such as strain gage torque measurements, to advanced custom multichannel systems. Accumetrics, Inc. is a subsidiary of PCB Piezotronics, Inc., and PCB® is a wholly owned subsidiary of MTS Systems Corporations.

© 2019 Accumetrics, Inc. In the interest of constant product improvement, specifications are subject to change without notice. PCB®, ICP®, Swiveler®, Modally Tuned®, and IMI® with associated logo are registered trademarks of PCB Piezotronics, Inc. in the United States. ICP® is a registered trademark of PCB Piezotronics Europe GmbH in Germany and other countries. UHT-12™ is a trademark of PCB Piezotronics, Inc. SensorLine™ is a service mark of PCB Piezotronics, Inc. SWIFT® is a registered trademark of MTS Systems Corporation in the United States. All other trademarks are property of their respective owners.

MD-0423 revNR 0719



MTS Sensors, a division of MTS Systems Corporation (NASDAQ: MTSC), vastly expanded its range of products and solutions after MTS acquired PCB Piezotronics, Inc. in July, 2016. PCB Piezotronics, Inc. is a wholly owned subsidiary of MTS Systems Corp.; IMI Sensors and Larson Davis are divisions of PCB Piezotronics, Inc.; Accumetrics, Inc. and The Modal Shop, Inc. are subsidiaries of PCB Piezotronics, Inc.