



HYDRO POWER TURBINE GENERATOR ROTOR MONITORING

KEEPING A WATCHFUL EYE ON HYDRO GENERATOR TEMPERATURES

Application: Hydro Power Turbine Generator Rotor Monitoring

Keeping a Watchful Eye on Hydro Generator Temperatures

Industry: Power

Product: [AT-7000](#) Motor Monitor

Parameters measured: Temperature

When a major hydro power producer needed to monitor the temperature of its generator's rotor poles and amortisseurs, Accumetrics provided multiple eight channel telemetry systems, each providing telemetry for eight installed RTD's. Although operating in close conjunction to large magnetic fields, Accumetrics digital telemetry was immune to EMI, and furthermore was able to provide proprietary sampling techniques to successfully and accurately capture all of the RTD data, providing clean, dependable analog temperature information from the Receiver. A robust transmitter was mounted onto the 43" diameter rotor shaft. This transmitter provided the excitation to the RTD's, and provided the signal conditioning and on-shaft high speed sampling (to properly capture the signal and noise components) needed for this application. The power and data were transferred through use of an induction coil set. The rotating coil was fabricated from four glass laminate 1/4-arc segments, while the 44" stationary pickup was of copper tubing segment construction. The digital data was converted to both current loop and voltage analog outputs at the Receiver, where output filtering eliminated the noise and presented clean, live temperature signals.



The above left picture shows the rotating Transmitter for the 8 RTD's (cover removed to show connections for the RTD's), the induction power/data coils (during testing in Schenectady) in the center, and the Receiver (digital to analog output device) on the right. The Receiver is equipped with optional panel meters providing $y=mx+b$ unit translation (analog voltage to scaled temperature outputs).

The AT-7000/ Motor Monitor can also be configured to additionally measure rotor voltages and currents, detect ground faults, and monitor shaft torque and torsional vibration. The Motor Monitor is a variation of the AT-7000 product line.



6 British American Boulevard, Suite 103-F, Latham, NY 12110 USA

accumetrix.com | telemetry@pcb.com | 888 684 0012 | +1 518 393 2200

© 2021 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevo is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevo), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.

MD-0419 revNR 0719